## BEST AVAILABLE COP

## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

05-226125

(43) Date of publication of application: 03.09.1993

(51)Int.CI.

H01F 1/053 C21D 6/00 C23C 18/32 C25D 3/12 H01F 1/08

(21)Application number : **04**-

(71)Applicant: KOBE STEEL LTD

061449

(22)Date of filing:

14.02.1992 (72)Inventor: NAKAYAMA

NAKAYAMA TAKENORI

SATO FUMIHIRO HANAKI ATSUSHI

## (54) MANUFACTURE OF HIGHLY CORROSION-RESISTANT RARE-EARTH MAGNET

(57)Abstract:

PURPOSE: To prevent occlusion of hydrogen into a magnet and a plated layer and hydrogen fragility of a magnet and then maintain high corrosion resistance and high-level magnetic characteristics over a long period of time by heating a rare-earth magnet subjected to Ni or Ni alloy plating within vacuum.

CONSTITUTION: RE-B-Fe sintered rare-earth magnet or RE-TM-B hot machining rare-earth magnet (RE indicates one or more kinds of rare-earth elements and TM indicates one or more kinds of transition elements) which is subjected to Ni on Ni alloy plating is heated within vacuum at a temperature which is equal to or higher than 600° C and less than 800° C.

## **LEGAL STATUS**

[Date of request for examination]
[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]
[Date of final disposal for application]
[Patent number]
[Date of registration]
[Number of appeal against examiner's decision of rejection]
[Date of requesting appeal against examiner's decision of rejection]
[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office